



140F/29

| FRAME SPECIFICATIONS |                             | S     | M     | L     | TECH SPECIFICATIONS           |   | ALL        |
|----------------------|-----------------------------|-------|-------|-------|-------------------------------|---|------------|
| A                    | TOP TUBE LENGTH EFFECTIVE   | 599   | 629   | 662   | U                             | TRUNNION MOUNT [SHOCK LENGTH-STROKE]    | 205-57.5   |
| B                    | SEAT TUBE LENGTH            | 360   | 410   | 460   | V                             | MAX TIRE SIZE                           | 29x2.6     |
| C                    | CHAINSTAY LENGTH            | 448   | 448   | 448   | W                             | MIN TIRE SIZE                           | 27.5x2.6   |
| D                    | BB DROP                     | 30    | 30    | 30    | X                             | HEAD TUBE HS UPPER / LOWER ID           | 56/56      |
| E                    | SEAT TUBE ANGLE             | 77°   | 77°   | 77°   | Y                             | CRANK SPLINE                            | ISIS EBIKE |
| F                    | HEAD TUBE ANGLE             | 65.5° | 65.5° | 65.5° | Z                             | CHAINLINE SPEC & MAX CHAINRING          | 52-53      |
| G                    | HEAD TUBE LENGTH            | 95    | 105   | 120   | AA                            | ENGINE MAXON BIKEDRIVE AIR 1.8Kg        | 30 Nm      |
| H                    | FORK OFFSET                 | 42-44 | 42-44 | 42-44 | AB                            | MAIN BATTERY MAXON BIKEDRIVE AIR 1.2 Kg | 250 Wh     |
| I                    | FORK AC                     | 551   | 551   | 551   | AC                            | RANGE EXTENDER 1.2Kg [OPTIONAL]         | 252 Wh     |
| J                    | REACH                       | 445   | 475   | 505   |                               |   |            |
| K                    | STACK                       | 603   | 612   | 625   |                               |   |            |
| L                    | REAR TRAVEL [148/12 OLD]    | 130   | 130   | 130   | <b>MAX TIRE CLEARANCE</b><br> |   |            |
| M                    | FORK TRAVEL                 | 140   | 140   | 140   |                               |   |            |
| N                    | SEAT TUBE ID                | 34.9  | 34.9  | 34.9  |                               |   |            |
| O                    | MAX DROPPER POST USE        | 200   | 220   | 240   |                               |   |            |
| P                    | SEAT TUBE OD                | 38    | 38    | 38    |                               |   |            |
| Q                    | WHEELBASE                   | 1192  | 1226  | 1262  |                               |   |            |
| R                    | STANDOVER HEIGHT            | 788   | 788   | 788   |                               |   |            |
| S                    | BB HEIGHT                   | 344   | 344   | 344   |                               |   |            |
| T                    | BRAKE MOUNT PM180 [203 MAX] | 180   | 180   | 180   |                               |   |            |

ALL FRAME MEASUREMENTS UNITS IN MILLIMETERS [mm]

